

DYMAX WORK TOOLS

TREE SHEARS FOR EXCAVATORS

OVERVIEW

A Dymax Excavator Tree Shear is the perfect tool for forest utility work, hazardous fuel removal from forest lands, plantation thinning of acacia and eucalyptus, biomass fuels production and trimming limbs and trees for roadside maintenance and site development or alongside railroad tracks.

In plantation thinning operations of Acacia and Eucalyptus a Dymax Excavator Tree Shear can average between 100 to 180 trees per hour cutting rates and produce more volume of wood than competing models. Cutting rates are subject to tree spacing, operators, and terrain.



FEATURES

- Bolt on replaceable AR400 razor sharp cutting knives yield up to 1,000 hours of performance and are easily sharpened when worn. All cutting knives are adjustable.
- Heavy duty cylinder rams with guarded lines.
- Two fabricated steel grapple arms secure trees to control felling and are powered by two (2) cylinder rams.
- Heavy duty blade carrier shear arms feature oversized chrome plated pivot pins with replaceable bushings.
- Bolt on guards protect hose lines and all hoses are wrapped with protective covering.
- Optional 60° hydraulic tilt left and right

OPTIONAL BUNCHING ARM



Options include a bunching arm gatherer that cuts multiple stems in specific operations.

Optional single bunching arm available for 14in, 16in and 18in models.



SPECIFICATIONS



Machine Size	Model No.	Description	Weight (lbs)	Optional Hydraulic Tilt	Weight (lb)
			No Tilt		With Tilt
12T/18T	DX-TS-FG-12in-HX	Tree Shear - Grapple - 12 in (30cm) Max Shearing Capacity - Hydraulic Excavator	2,000	Yes; 60°	2,600
14T/20T	DX-TS-FG-14in-HX	Tree Shear - Grapple - 14 in (36cm) Max Shearing Capacity - Hydraulic Excavator	2,600	Yes; 60°	3,200
15T/25T	DX-TS-FG-16in-HX	Tree Shear - Grapple - 16 in (41cm) Max Shearing Capacity - Hydraulic Excavator	2,800	Yes; 60°	3,400
20T/30T	DX-TS-FG-18in-HX	Tree Shear - Grapple - 18 in (46cm) Max Shearing Capacity - Hydraulic Excavator	4,700	Yes; 60°	5,600
22T/36T	DX-TS-FG-20in-HX	Tree Shear - Grapple - 20 in (51cm) Max Shearing Capacity - Hydraulic Excavator	5,300	Yes; 60°	6,100
14T/20T	DX-TS-FB-14in-HX	Tree Shear - Bunching - 14 in (36cm) Max Shearing Capacity - Hydraulic Excavator	2,900	Yes; 60°	3,450
15T/25T	DX-TS-FB-16in-HX	Tree Shear - Bunching - 16 in (41cm) Max Shearing Capacity - Hydraulic Excavator	3,100	Yes; 60°	3,700
25T/30T	DX-TS-FB-18in-HX	Tree Shear - Bunching - 18 in (46cm) Max Shearing Capacity - Hydraulic Excavator	5,600	Yes; 60°	6,500



DYMAX INC
402 Miller Drive
Wamego, KS 66547 USA

Toll Free: 800.530.5407 (USA/CAN)
Office: +1.785.456.2081
Fax: +1.785.456.8328

www.DYMAXINC.com
sales@DYMAXINC.com